

# FIRG / ISO A SERIES ADAPTOR

## SPECIALTY COUPLING

The **FIRG / ISO A Series Adaptor** provides dimensional compatibility between old and new equipment by adapting imperial nominal size to ISO metric size in a flat face coupler. This avoids changing mismatched couplers, saving time and resources. These bidirectional flow adapters are ideal in systems with high pressure that require reliable and leak-free coupling.



### FEATURES


**Size range:** 1/2"

**Working pressure:** 250 bar/3750 psi

- Provides compatibility between old and new equipment
- Avoids changing mismatched couplers
- Bidirectional flow

### APPLICATIONS

- Wherever several "generations" of equipment exist
- High-pressure situations that require reliable, leak-free connection





### Adapter Couplers Flat Face/ISO A | 8036-Adapter

DESCRIPTION	ORDER CODE	INSCRIPTION
1/2 FEMALE FLAT FACE / 1/2 MALE ISO A	803622000	F. FIRG 12A M. BIR12
1/2 MALE FLAT FACE / 1/2 FEMALE ISO A	803622001	M. FIRG 12A F. BIR12



F. FIRG12A  
M. BIR12

DESCRIPTION	NOMINAL SIZE	ISO SIZE	MAX. WORKING PRESSURE	MAX. WORKING PRESSURE
VEP	inch	mm	bar	psi
F. FIRG12A M. BIR12	1/2	12.5	250	3750
M. FIRG12A F. BIR12	1/2	12.5	250	3750



M. FIRG12A  
F. BIR12